

CONTINENTAL LINE STANDARD LOCKING RAIL



Innovation | Dedication | Reliability | Safety

PRODUCT INFORMATION

FEATURES

- Mounts to stage floor or fly gallery standards on 5' 0" centers
- Index strip and card holders
- Built to withstand a 300 pound per linear foot up load

DESCRIPTION

Located at the stage floor or fly floor level, Locking Rail assemblies are used for mounting rope locks. Supplied with an index card strip and card holders for set identification. Rear illuminated index strip available by request when order placed. Locking rail assemblies are available for single and double purchase sets with rigid t-bar guides, and for single wire guide sets. Built to withstand a 300 pound per linear foot up load. Rail assemblies must be securely anchored to the stage floor or grid as required to withstand both the uplift and lateral loads.

SPECIFICATIONS

Angles shall be minimum 3" x 3" with holes to accept lock for each potential set whether rigged or supplied or not at this time. An index strip of 3" x 3/16" strap shall be secured to the stage side at approximately 45 degree angle. Card holders shall be supplied each ____". Dividers shall be fastened with bolts, and shall return under strap to keep cards from falling out. Wing nuts and lock washers shall be used under the strap to secure the dividers. Standard Locking Rail, Catalog No. TLR0000-00 as fabricated by Tiffin Scenic Studios, Inc. Tiffin, Ohio.



Standard Locking Rail
Catalog No. SLR0000-00

